

## AMERICAN TOOTH INDUSTRIES

1200 Stellar Drive ● Oxnard, CA 93033-2404 ● (805) 487-9868 Corporate e-mail: info@americantooth.com ● www.americantooth.com

#### SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME

Justi Tooth Shades Cold/Cure Resin Powder

Product Description Plasticized Polymethyl Methacrylate/Copolymer

Blend

**Manufacturer** American Tooth Industries

1200 Stellar Drive Oxnard, CA 93033 805-487-9868

Emergency Phone Number: Infotrac: 800-352-5053

**Recommended use** Specially prepared formulation for dental

laboratories to construct and build strong temporary crowns and bridges. Crosslinking monomer with high craze resistance and toughness. Kit available

in Imperial shades.

**Restrictions on use** Industrial Use Only

## 2. HAZARDS IDENTIFICATION

Hazard classification Physical, Health, Environmental

Eye Damage/Irritation-Category 2A Reproductive Toxicity-Category 2 Aquatic Toxicity-Category A3

Signal Word Warning

Hazard Statements H319 Causes serious eye irritation

H361 Suspected of damaging fertility or the

unborn child

H402 Harmful to aquatic life

**Symbol** 





Form 244 Rev 9/11/15 Page **1** of **8** 

**Precautionary statements** 

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions

have been read and understood

P264 Wash hands and exposed skin thoroughly

after handling

P273 Avoid release to the environment P280 Wear protective gloves/protective clothing/eye protection/face protection P281 Use personal protective equipment as

required

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing P308+P313 IF exposed or concerned: Get medical

advice/attention

P337+P313 Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container to an

authorized disposal facility

Other hazards N/A

## 3. COMPOSTITION/INFORMATION ON INGREDIENTS

Statement for unknown toxicity N/A

Chemical name Polymethyl Methacrylate

Common name/synonyms N/A

Impurities and stabilizing additives

Chemical Name	Weight- %	CAS Number
Polymethyl Methacrylate	70-80	9011-14-7
Diethyl Phthalate	10-20	84-66-2
2-Propenoic acid, 2-methylethyl ester, polymer with methyl 2-methyl-2propenoate	5-10	25685-29-4

<sup>\*</sup>Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret is required

## 4. FIRST AID MEASURES

**General Advice** 

Provide the SDS to medical personnel for treatment.

treatment.

Form 244 Rev 9/11/15 Page **2** of **8** 

**Inhalation** Remove victim to fresh air. Seek immediate

medical attention.

**Skin Contact** Rinse thoroughly with lukewarm water, followed by

a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists,

contact a physician immediately.

Eye Contact If product gets in the eyes, flush with lukewarm

water for at least 15 minutes. If irritation occurs,

contact a physician.

**Ingestion** If ingested, do not induce vomiting. If product has

been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get

medical attention immediately.

Most important symptoms or effects, both acute and delayed:

N/A

Indication of immediate medical attention and special treatment needed:

N/A

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Water, Chemical (alcohol-resistant) foam, dry

chemical, or carbon dioxide.

Unsuitable extinguishing media Not known

**Special hazards arising from substance** Polymers are combustible dusts, care should be

taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures.

Special protective equipment and Precautions for fire fighters

Polymer dust is combustible. The explosive limits of

the polymer particles suspended in air are approximately those of coal dust. Polymers are sensitive to static discharge, follow grounding and bounding procedures. Polymers are not sensitive to

mechanical impacts.

Form 244 Rev 9/11/15 Page **3** of **8** 

## Personal precautions, protective equipment and emergency procedures

Before cleaning any spill or leak, individuals must wear appropriate Personal Protective Equipment that is specified in section 8. Keep airborne particulates at a minimum when cleaning up spills. Deny entry to all unprotected individuals. Remove any contaminated clothing and wash thoroughly before reuse.

#### **Environmental precautions**

Extinguish all ignition sources. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

#### Methods and materials for containment

Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material (e.g. sand or earth). May contaminate water supply.

#### Methods and materials for cleaning up

Maximize ventilation (open doors and windows) and secure all sources of ignition. Use good, local ventilation with a minimum capture velocity of 100 ft/min (30 m/min) at point of product release. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Not a RCRA Hazardous waste.

## 7. HANDLING AND STORAGE

## Handling

Use in well ventilated areas. Avoid contact with skin, eyes and clothing. Avoid breathing dust. Use good personal hygiene and housekeeping. Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

#### Storage

Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat.

#### Storage temperature

The temperature should remain at or under 72°F (22°C) at all times.

#### Incompatible materials

Strong oxidizers, strong oxidizing agents.

Form 244 Rev 9/11/15 Page **4** of **8** 

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Polymethyl Methacrylate 9011-14-7			
Diethyl Phthalate 84-66-2		5 mg/m3 TWA	NIOSH: 5 mg/m3 TWA
2-Propenoic acid, 2-methyl-, ethyl ester, polymer with methyl 2-methyl-2-propenoate 25685-29-4			

#### **Appropriate Engineering Controls**

Use local explosion-proof ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceClearOdorFaintBoiling Range295 °C

**Flash Point** 579°F, 304°C **Evaporation Rate** No data available

**Upper/Lower Flammability limits** 0%

## 10. STABILITY AND REACTIVITY

Reactivity N/A
Chemical Stability Stable

**Hazardous Reactions**Hazardous polymerization will not occur.

Conditions to avoid N/A

Materials to avoid Strong oxidizers

Hazardous Decomposition Products Methacrylate Monomer and Oxides of Carbon when

burned.

## 11. TOXILOGICAL INFORMATION

# Mixture Toxicity Component Toxicity

## **Effects of Chronic Exposure**

## Carcinogenicity

Dibutyl Phthalate is listed by the EPA and OSHA as a possible carcinogen. None of the other components of this material are listed by IARC, NTP, OSHA, or ACGIH as carcinogens.

#### **Reproductive Toxicity**

Women working where phthalates are used had higher incidence of miscarriages, menstrual disorders, and reduced gestation periods.

Form 244 Rev 9/11/15 Page **5** of **8** 

#### **Teratogenicity**

Dibutyl Phthalate may cause fetal effects based on animal studies.

#### **Mutagenicity Data**

This product is not reported to produce mutagenic effects in humans.

#### Identify likely routes of exposure:

 Inhalation
 N/A

 Ingestion
 N/A

 Skin
 N/A

 Eye
 N/A

Description of delayed, immediate or chronic effects from short term and long term exposure:

N/A

#### **Description of symptoms:**

N/A

#### 12. ECOLOGICAL INFORMATION (If available)

Very large releases of this product is harmful or fatal to overexposed aquatic life.

#### **Component Ecotoxicity**

Diethyl Phthalate 96 Hr LC50 Pimephales promelas: 17 mg/L [flow

through]; 96 Hr LC50

Pimephales promelas: 16.8 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 22 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 16.7

mg/L [static]; 96 Hr

LC50 Oncorhynchus mykiss: 12 mg/L [flow-

through]

48 Hr EC50 Daphnia magna: 36 - 74 mg/L; 48 Hr

EC50 Daphnia magna: 86 mg/L [Static]

72 Hr EC50 Desmodesmus subspicatus: 23 mg/L; 72 Hr EC50 Desmodesmus subspicatus: 23 mg/L [static]; 96 Hr EC50 Desmodesmus subspicatus: 21 mg/L; 96 Hr EC50 Desmodesmus subspicatus: 21

mg/L [static]; 72 Hr EC50

Pseudokirchneriella subcapitata: 42 - 255 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: 2.11 -

4.29 mg/L [static]

## 13. DISPOSAL CONSIDERATIONS (If applicable)

#### **Waste Treatment Methods**

#### **Disposal of Wastes**

Dispose waste material in accordance with Federal, State, and Local regulations. It is the responsibility of the generator to determine at the time of disposal whether the product meets

Form 244 Rev 9/11/15 Page **6** of **8** 

the criteria of a hazardous waste. Comply with all applicable federal, state and local regulations. Waste disposal options include landfilling solids at permitted sites. Incinerate in a chemical incinerator equipped with an afterburner and scrubber. Use registered transporters.

## **Contaminated Packaging**

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations

## 14. TRANSPORT INFORMATION (If applicable)

Agency	Proper Shipping Name	<b>UN Number</b>	<b>Packing Group</b>	<b>Hazard Class</b>
DOT	Not Regulated, Polymer, NOS			_
IATA	Not Regulated, Polymer, NOS			
IMDG	Not Regulated, Polymer, NOS			

## 15. REGULATORY INFORMATION (If available)

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

#### **SARA 313**

- None

## **US State Right-to-Know Regulations**

- None

<u>Country</u> <u>Regulation</u> <u>All Components Listed</u>


EINECS Yes
SARA Hazard categories No
TSCA Inventory Yes

## **16. OTHER INFORMATION**

#### Hazardous Material Information System (HMIS)

HEALTH	1		HMIS & NFPA Hazard Ratin Legend  * = Chronic Health Hazard 0 = INSIGNIFICANT	
FLAMMABILITY	1			
PHYSICAL HAZARD	0			
PERSONAL PROTECTION B			1 = SLIGHT 2 = MODERATE	
			3 = HIGH	

#### National Fire Protection Association (NFPA)



Date of Revision: 11/10/2015

Form 244 Rev 9/11/15 Page **7** of **8** 

American Tooth Industries believes that the information and recommendations contained herein (including data and statements) are accurate as of date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of American Tooth Industries expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

Form 244 Rev 9/11/15 Page **8** of **8**